

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Ideal to delineate or out of bounds areas
- > Durable and Easy to Apply

CONSTRUCTION

Backing: LDPE
Adhesive: -

COLOR(S)

 red - white

STANDARD SIZE

Widht(s): 75 mm
Length(s): 100m

Contact your BDT sales representative for other available sizes.



PHYSICAL PROPERTIES

	STANDARD VALUES	UNITS	TOLERANCE
Thickness	50	µm	(+/- 5%)
Tensile Strenght	N/A	-	-
Elongation	400	%	(+/- 20%)
Service Temperature Range	from -5 to +40	°C	-
	from 23 to 104	F	-

The following properties are typical and should not be considered specifications. All properties are approximate and are based on tests believed to be reliable and preformed conformance with recommended test methods. These values are presented for comparison purposes and do not represent a guarantee by the manufacturer. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry (not more than 21 °C (70 °F) and 50% relative humidity) away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.