

TECHNICAL DATA

ADVANTAGES AND BENEFITS

- > Does not stretch and shrink and remains stable
- > Highly resistant to most chemicals and solvents
- > No sliding effect

TYPICAL APPLICATIONS

- > For joining plasterboards
- > Repairing
- > Ideal for scratches and crackings

CONSTRUCTION

Backing: Mesh
Adhesive: Acrylic
Weaving: Lenov

COLOR(S)

White

STANDARD SIZE

Width(s): 48 mm
Length(s): 20m, 45m, 90m, 153m

Contact your BDT sales representative for other available sizes.



PHYSICAL PROPERTIES

		STANDARD VALUES	UNITS	TOLERANCE
Mesh size	Warp	8	mesh / inch	(+/- 8%)
	Weft	6	mesh / inch	(+/- 8%)
Adhesive		≥ 100	seconds	-
Elongation		≥ 0,8	%	-
Tensile Strenght	Warp	≥ 9,0	N/mm	-
	Weft	≥ 9,0	N/mm	-
Weight of finished product		48,5	g/m ²	(+/- 5 g/m ²)

The following properties are typical and should not be considered specifications. All properties are approximate and are based on tests believed to be reliable and preformed conformance with recommended test methods. These values are presented for comparison purposes and do not represent a guarantee by the manufacturer. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area (not more than 21 °C (70 °F) and 50% relative humidity) away from direct sunlight and should be user within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.