

MT 5210 GENERAL PURPOSE MASKING TAPE



TECHNICAL DATA

ADVANTAGES AND BENEFITS

- > Interior protection
- > The tape can stay on the masked area only for a short time

TYPICAL APPLICATIONS

- > Masking
- > Bundling
- > Holding
- > Packing

CONSTRUCTION

Overall Grade: Purpose Grade
Backing: Impregnated paper medium creping
Adhesive: Synthetic Rubber / Resins

COLOR(S)

White Yellow

STANDARD SIZE

Width(s): 25mm / 1", 38mm / 1.5", 48mm / 2"

Length(s): 50m / 60yd

Contact your BDT sales representative for other available sizes.



PHYSICAL PROPERTIES

	STANDARD VALUES	UNITS	TOLERANCE
Thickness	95	my	(+/- 10%)
Adhesion to Stainless Steel 180°	≥ 3	N/2,5cm	-
Tensile Strength	3,1	kg/cm	(+/- 2%)
Elongation	9	%	(+/- 2%)
Service Temperature Range	from -10 to +60	°C	-
	from 14 to 140	F	-

The following properties are typical and should not be considered specifications. All properties are approximate and are based on tests believed to be reliable and performed conformance with recommended test methods. These values are presented for comparison purposes and do not represent a guarantee by the manufacturer. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area (not more than 21 °C (70 °F) and 50% relative humidity) away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.