

TECHNICAL DATA

ADVANTAGES AND BENEFITS

> PE foil

TYPICAL APPLICATIONS

- > Protection of objects and surfaces
- > Protection during renovation works
- > General use

CONSTRUCTION

Backing: HDPE

COLOR(S)

Natural

STANDARD SIZE

Width(s): 2m
Length(s): 50m

Contact your BDT sales representative for other available sizes.



PHYSICAL PROPERTIES

	STANDARD VALUES	UNITS	TOLERANCE
Density	940 - 960	kg/m ³	-
Net weight	460	g	-

The following properties are typical and should not be considered specifications. All properties are approximate and are based on tests believed to be reliable and performed conformance with recommended test methods. These values are presented for comparison purposes and do not represent a guarantee by the manufacturer. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area (not more than 21°C (70°F) and 50% relative humidity) away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

The foil does not contain any hazardous substances. The foil meets the requirements of Directive 94/62 / EC.