

TECHNICAL DATA

ADVANTAGES AND BENEFITS

- > Excellent adhesion to many surfaces
- > Suitable for smooth and rough surfaces
- > Strong adhesive

TYPICAL APPLICATIONS

- > For joining or repairing films, nonwovens and membranes (PP)
- > Ideal for polyethylene, polypropylene films, nonwovens, PP membranes, steel, glass and foamed EPS

CONSTRUCTION

Backing: Non-woven fabric
Liner: Two sided silsconized paper
Adhesive: Based on rubber

COLOR(S)

■ Black

STANDARD SIZE

Widht(s): 50 mm
Length(s): 25m

Contact your BDT sales representative for other available sizes.



PHYSICAL PROPERTIES

| | STANDARD VALUES | UNITS | TOLERANCE |
|--|-----------------|---------|-----------|
| Adhesion to Stainless Steel 180° (after 20 min.) | 45 | N/2,5cm | (+/- 10%) |
| Tensile Strenght | ≥ 70 | N/in | - |
| Elongation | 50 | % | - |
| Service Temperature Range | from +5 to +75 | °C | - |
| | from 41 to 167 | F | - |

The following properties are typical and should not be considered specifications. All properties are approximate and are based on tests believed to be reliable and preformed conformance with recommended test methods. These values are presented for comparison purposes and do not represent a guarantee by the manufacturer. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry (from +5 °C to +30 °C (41 °F - 86 °F) and 70% relative humidity) away from direct sunlight and should be user within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.