

TECHNICAL DATA

ADVANTAGES AND BENEFITS

- > Strong adhesive
- > The slippery surface of the tape prevents it from sticking to the joining compound


TYPICAL APPLICATIONS

- > For sliding joints - prevents the formation of visible cracks in the plaster

CONSTRUCTION

Backing: BOPP
Adhesive: Hot melt

COLOR(S)

 White with print

STANDARD SIZE

Width(s): 48mm
Length(s): 50m

Contact your BDT sales representative for other available sizes.



WŁAŚCIWOŚCI FIZYCZNE

	STANDARD VALUES	UNITS	TOLERANCE
Thickness	37	µm	(+/- 10%)
Adhesion to Stainless Steel 180°	≥ 4	N/cal	-
Hold	≥ 120	h	-
Tensile Strength	140	N/mm ²	(+/- 10%)
Break point	140	%	(+/- 20%)
Service Temperature Range	from 0 to +40	° C	-
	from 32 to 104	F	-

The following properties are typical and should not be considered specifications. All properties are approximate and are based on tests believed to be reliable and performed conformance with recommended test methods. These values are presented for comparison purposes and do not represent a guarantee by the manufacturer. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area (10°C - 40°C (50°F - 104°F) and 50% relative humidity) away from direct sunlight and should be used within 6 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.