

TECHNICAL DATA

ADVANTAGES AND BENEFITS

> Two-layer cardboard

TYPICAL APPLICATIONS

- > Protection of objects and surfaces
- > Protection during renovation works
- > General use

CONSTRUCTION

Backing: Two-layer cardboard

COLOR(S)

 Silver

STANDARD SIZE

Widht(s): 1 m.

Length(s): 15 m.

Contact your BDT sales representative for other available sizes.



PHYSICAL PROPERTIES

	STANDARD VALUES	UNITS	TOLERANCE
Grammage	180	g/m ²	± 5 %
Thickness	2,5	mm	-

The following properties are typical and should not be considered specifications. All properties are approximate and are based on tests believed to be reliable and performed conformance with recommended test methods. These values are presented for comparison purposes and do not represent a guarantee by the manufacturer. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Cardboard should be stored in its original packaging in a cool, dry area (5°C - 25°C (50°F - 104°F) and 40 - 60% relative humidity) away from direct sunlight. The product is sensitive to changes in temperature and humidity in winter. Surfaces to which cardboard is applied should be clean, dry and free of grease, oil or other contaminants. The product is flammable.